

DKS-3000

Single docking station for SKY3000



Product overview

DKS- 3000 provides bump testing and calibration for one unit SKY3000 on a single-unit station. It also maintains the all important event logs that demonstrate users are working within company requirements. It supports data export through U-DISK, simple, user friendly and functional.

Product Advantage

- Bump testing, calibration, configuration and data recording on a single station
- Fast - up to 1 units bumped or calibrated simultaneously
- Portable, using battery power for up to 3000 bump tests
- Upgrades Docking Firmware
- Robust - All-in-one hard case
- With 32G SD card, more than 10,000 sets data can be recorded
- Saves the bump ,calibration,configuration data in station and support U-disk connesction for data and calibration report export
- Includes Safegas PC software for easy configuration and data analysis

Technical parameters

Unit Compatibility	SKY3000 multi 4(CO,O2,H2S,LEL)in 1 standard gas detector
Operating Temperature	5-40° C
Sampling type	Pumped
Calibration gas access mode	NA, the calibration gas is directly connected to the SKY3000 detector
Communication mode	UART to USB, MicroUSB interface
Button	3 buttons, Bump, cali and power buttons
LEDS	5 red/green color LEDS
Battery type	Rechargeable Lithium Ion
Memory	Built-in 32G SD card
Supported Gas	CO/H2S/O2/CH4,4 gases need to do at the same time
Power supply	DC12V
Events stored	Bump/Calibration logs, Configurations
Data export	Removable U-disk, Type-A interface
Output interface	UART-USB, MicroUSB interface
Standard accessory	User Manual, flowmeter, T-shape,Charger, Data wire
Optional accessory	Pressure regulator, U disk
Material	ABS+metal+nylon
Weight	4.2kgs
Size	329x312x123mm